



Attaches Wood to Wood Lengths 1-1/4" - 3" WAR Coated

Square Drive Bugle Head Coarse Thread

> Attaches Wood to Wood Lengths 1-5/8" - 3-1/2" WAR Coated

Star Drive Flat Head w/Nibs **Coarse Thread**



Phillips Flat Head Reamer w/Wings



305 Stainless **Bugle Head Coarse Thread**

> Attaches Wood to Wood **Lengths** 1-1/4" - 3"

305 Stainless Flat Head w/Nibs **Coarse Thread**

Attaches Wood to Wood Lengths 1-1/4" - 4"

305 Stainless Trim Head **Coarse Thread**

> Attaches Wood to Wood Lengths 1-5/8" - 3"

316 Stainless Flat Head w/Nibs **Coarse Thread**

410 Stainless **Flat Head** Reamer w/Wings

Attaches Wood to Metal **Lengths**



2-1/2" - 3-1/4"

INTERCORP <

 Los Angeles
 New York
 Chicago
 Dallas
 Atlanta
 Portland
 Houston
 Cleveland
 Miami

 800.762.2004
 888.322.2262
 800.533.9669
 800.558.7222
 800.822.9690
 800.434.5606
 800.558.7222
 800.533.9669
 800.822.9690

Attaches Wood

2-1/2" - 3-<u>1/2</u>"

to Wood

Lengths





Phillips Bugle Head, Coarse Thread, WAR Coated



- Meets ASTM A 510 for carbon steel manufacturing
- Meets ASTM ASTM B-117 for salt spray corrosion testing
- · Designed to work with ACQ treated lumber
- · Exceeds 1,000/hr. salt spray resistance

Material Application

Exterior wood screw for outdoor applications. Attaches wood to wood.



Size	Bulk Part No	Bulk Qty	Lbs*	5lb Part No	5lb Qty	1lb Part No	1lb Qty
6 x 1-1/4	614CW	8M	29	614CWV	1,300	614CWI	250
6 x 1-5/8	615CW	5M	22	615CWV	1,000	615CWI	200
6 x 2	620CW	3.5M	19	620CWV	700	620CWI	175
8 x 2-1/2	822CW	2.5M	22	822CWV	400	822CWI	100
8 x 3	830CW	2M	21	830CWV	400	830CWI	100

Square Drive Bugle Head, Coarse Thread, Type '17', WAR Coated



- · Meets ASTM A 510 for carbon steel manufacturing
- · Designed to work with ACQ treated lumber
- Exceeds 1,000/hr. salt spray resistance
- Type '17' reduces wood splitting and eliminates the need for pre-drilling

Material Application

Exterior wood screw for outdoor applications. Attaches wood to wood.



Size	Bulk Part No	Bulk Qty	Lbs*	5lb Part No	5lb Qty	1lb Part No	1lb Qty
6 x 1-5/8	XQ615W	5M	22	XQ615WV	1,000	XQ615WI	200
6 x 2	XQ620W	3.5M	19	XQ620WV	700	XQ620WI	175
8 x 2-1/2	XQ822W	2.5M	22	XQ822WV	400	XQ822WI	100
8 x 3	XQ830W	2M	21	XQ830WV	400	XQ830WI	100
10 x 3-1/2	XQ1031W	1M	18	XQ1031WV	250	XQ1031WI	50

Star Drive Flat Head w/Nibs, Coarse Thread, Type '17', WAR Coated



- · Star drive prevents cam out and stripping for improved driveability
- · Designed to work with ACQ treated lumber
- Exceeds 1,000/hr. salt spray resistance
- Type '17' reduces wood splitting and eliminates the need for pre-drilling

Material Application

Exterior wood screw for outdoor applications. Attaches wood to wood.



Size	Bulk Part No	Bulk Qty	Lbs*	5lb Part No	5lb Qty	1lb Part No	1lb Qty
8 x 1-1/4	XT814W	8M	38	XT814WV	1,000	XT814WI	200
8 x 1-5/8	XT815W	5M	30	XT815WV	800	XT815WI	150
8 x 2	XT820W	3.5M	25	XT820WV	700	XT820WI	140
9 x 2-1/2	XT922W	2.5M	26	XT922WV	400	XT922WI	100
9 x 3	XT930W	2M	24	XT930WV	400	XT930WI	100
10 x 3-1/2	XT1031W	1M	17	XT1031WV	250	XT1031WI	50
10 x 4	XT1040W	.8M	16	XT1040WV	250	XT1040WI	50
10 x 5	XT1050W	.5M	13	XT1050WV	200	XT1050WI	40
10 x 6	XT1060W	.5M	15	XT1060WV	125	N/A	N/A





Phillips Flat Head Reamer w/Wings, WAR Coated

• Meets ASTM C 1513 for cold-formed steel framing connections

• Meets F.I.P.-1000.7 for torsional strength & drill speed

- Exceeds 1,000/hrs. salt spray resistance
- · For use in pressure treated lumber
- Wings ream hole in wood preventing "jacking action"
- · Used for attaching lumber or headers to steel





Size	Pt	Bulk Part No	Bulk Qty	Lbs*	Drill Cap (in.)	Wood Range	5lb Part No	5lb Qty	1lb Part No	1lb Qty
12-24 x 2	3	R200W	2M	32	.110210	1/2" - 1-1/8"	R200WV	300	R200WI	50
12-24 x 2-1/2	4	R212W	1.5M	30	.110250	1/2" - 1-1/2"	R212WV	250	R212WI	50
1/4-20 x 2-3/4	4	R234W	1M	30	.110375	3/4" - 1-3/4"	R234WV	165	R234WI	30
1/4-20 x 3-1/4	4	R314W	1M	35	.110375	3/4" - 2-1/4"	R314WV	150	R314WI	30
1/4-20 x 3-1/2	4	R312W	.8M	30	.110375	3/4" - 2-1/2"	R312WV	130	R312WI	25
1/4-20 x 3-3/4	4	R334W	.5M	20	.110375	3/4" - 2-3/4"	R334WV	125	R334WI	25
1/4-20 x 4-3/4	4	R434W	.5M	27	.110375	3/4" - 3-3/4"	R434WV	100	R434WI	20

305 Stainless Steel Phillips Bugle Head, Coarse Thread



- · For fencing, decks, patio furniture, spas
- · High degree of corrosion resistance

Material Application

Exterior wood screw for outdoor applications. Attaches wood to wood.

Size	Bulk Part No	Bulk Qty	Lbs*	5lb Part No	5lb Qty	1lb Part No	1lb Qty
8 x 1-1/4	814CSS	8M	40	814CSSV	1,000	814CSSI	200
8 x 1-5/8	815CSS	5M	31	815CSSV	750	815CSSI	150
8 x 2	820CSS	3.5M	25	820CSSV	500	820CSSI	100
8 x 2-1/2	822CSS	2.5M	23	822CSSV	400	822CSSI	100
8 x 3	830CSS	2M	22	830CSSV	400	830CSSI	80

305 Stainless Steel Star Drive Flat Head w/Nibs, Coarse Thread, Type '17'

- Star drive prevents cam out and stripping for improved driveability
- Superior penetration through a variety of woods
- · High degree of corrosion resistance
- · Nibs under head provide flush finish
- Type '17' reduces wood splitting and eliminates the need for pre-drilling

Material Application

Exterior wood screw for outdoor applications. Attaches wood to wood.



Size	Bulk Part No	Bulk Qty	Lbs*	5lb Part No	5lb Qty	1lb Part No	1lb Qty
8 x 1-1/4	XT814SS	5M	23	XT814SSV	1,000	XT814SSI	200
8 x 1-5/8	XT815SS	4M	23	XT815SSV	800	XT815SSI	160
8 x 2	XT820SS	3M	22	XT820SSV	700	XT820SSI	150
10 x 2-1/2	XT1022SS	2M	24	XT1022SSV	400	XT1022SSI	80
10 x 3	XT1030SS	1.5M	22	XT1030SSV	300	XT1030SSI	60
10 x 3-1/2	XT1031SS	1M	17	XT1031SSV	250	XT1031SSI	50
12 x 4	XT1240SS	1M	28	XT1240SSV	165	XT1240SSI	40





305 Stainless Steel Square Drive Trim Head, Coarse Thread, Type '17'



- Superior penetration through a variety of woods
- · High degree of corrosion resistance
- Type '17' reduces wood splitting and eliminates the need for pre-drilling

Material Application

Exterior wood screw for attaching trim and rails to decks or fences.

Size	Bulk Part No	Bulk Qty	Lbs*	5lb Part No	5lb Qty	1lb Part No	1lb Qty
7 x 1-5/8	X1QSS	5M	29	X1QSSV	1,000	X1QSSI	200
7 x 2-1/4	X2QSS	3M	23	X2QSSV	600	X2QSSI	125
7 x 3	X3QSS	2M	21	X3QSSV	500	X3QSSI	100

305 Stainless Steel Star Drive Trim Head, Coarse Thread, Type '17'

- · Star drive prevents cam out and stripping for improved driveability
- · Superior penetration through a variety of woods
- · High degree of corrosion resistance
- Type '17' reduces wood splitting and eliminates the need for pre-drilling

Material	Application
mattiai	Application

Exterior wood screw for attaching trim and rails to decks or fences.

Size	Bulk Part No	Bulk Qty	Lbs*	5lb Part No	5lb Qty	1lb Part No	1lb Qty
7 x 1-5/8	X1TSS	5M	29	X1TSSV	1,000	X1TSSI	200
7 x 2-1/4	X2TSS	3M	23	X2TSSV	600	X2TSSI	125
7 x 3	X3TSS	2M	21	X3TSSV	500	X3TSSI	100

316 Stainless Steel Star Drive Flat Head w/Nibs, Coarse Thread, Type '17' NEW ITEM!

- Star drive prevents cam out and stripping for improved driveability
- Superior penetration through a variety of woods
- Maximum degree of corrosion resistance
- · Nibs under head provide flush finish
- Type '17' reduces wood splitting and eliminates the need for pre-drilling

Material Application

Exterior wood screw for outdoor applications. Attaches wood to wood.





410 Stainless Steel Star Drive Flat Head Reamer w/Wings, Strong-Shield Coated

- Meets ASTM C 1513 for cold-formed steel framing connections
- · Meets F.I.P.-1000.7 for torsional strength & drill speed
- Meets SAE J78 for performance & dimensional specifications
- · Rust/Acid Rain Protection
- ACQ Compatible
- Exceeds 1,000/hr. salt spray resistance

Material Application
Attaches wood to metal.



Size	Pt	Bulk Part No	Bulk Qty	Lbs*	Drill Cap (in.)	Wood Range	5lb Part No	5lb Qty	1lb Part No	1lb Qty
12-24 x 2-1/2	4	4RT212	1M	21	.110375	1/2" - 1-1/2"	4RT212V	250	4RT212I	50
1/4-20 x 2-3/4	4	4RT234	.8M	24	.110375	1/2" - 1-3/4"	4RT234V	160	4RT234I	30
1/4-20 x 3-1/4	4	4RT314	.5M	17	.110375	3/4" - 2-1/4"	4RT314V	125	4RT314I	25

